SAFETY DATA SHEET

SDS No.1021-58011 Date June 21, 2023 1/6 page

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : Car Interior VOC Standard Mixed Sample 10µg/mL in Ethanol

NAME OF SUPPLIYER : GL Sciences Inc.

ADDRESS : 22-1 Nishishinjuku 6-chome Shinjuku-ku Tokyo 163-1130, Japan

CHARGE SECTION : International Sales Section

TELEPHONE No. : +81-3-5323-6620 FACSIMILE No. : +81-3-5323-6621 PRODUCT No. : 1021-58011, 1021-SDS No. : 1021-58011

Research use only.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION : Flammable liquid : Category 2

Serious eye damage/eye irritation : Category 2
Carcinogenicity : Category 1A
Reproductive toxicity : Category 1A

Specific target organ toxicity

(Single exposure) : Category 3(Airway irritation,

Anesthetic effect)

Specific target organ toxicity

(Repeated exposure) : Category 1(Liver)

: Category 2(Central nervous system)

HAZARD SYMBOL







SIGNAL WORD : Danger

HAZARD STATEMENTS

H225 Highly flammable liquid and vapour

H319 Strong eye irritation H350 May cause cancer

H360 May damage fertility or the unborn child

H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness

H372 Cause damage to organs through prolonged or repeated exposureH373 May cause damage to organs through prolonged or repeated exposure

<central nervous system>

PRECAUTIONARY STATEMENTS:

[Prevention]

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. –No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe fume/gas/mist/vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

PRODUCT NAME : Car Interior VOC Standard Mixed Sample 10µg/m L in Ethanol

SDS No.1021-58011 Date June 21, 2023 2/6 page [Response] P303+P361+ P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower. P370+P378 In case of fire: Use appropriate media such as chemical powder or carbon dioxide to extinguish. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact P305+ P351+ P338 lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical attention. IF exposed or concerned: Get medical advice/attention. P308+P313 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P314 Get medical attention if you feel unwell. [Storage] P403+ P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 Store locked up. [Disposal] P501 Dispose of contents/container in accordance with all applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL IDENTITY : Mixture

CHEMICAL NAME	CONTENT	CHEMICAL FORMULA	CAS RN	TSCA INVENTRY	EINECS No.
Ethanol	99.991 %	C ₂ H ₅ OH	64-17-5	Listed	200-578-6
Toluene	0.001 %	C6H5CH3	108-88-3	Listed	203-625-9
o-Xylene	0.001 %	C6H4(CH3)2	95-47-6	Listed	202-422-2
m-Xylene	0.001 %	C6H4(CH3)2	108-38-3	Listed	203-576-3
p-Xylene	0.001 %	C6H4(CH3)2	106-42-3	Listed	203-396-5
Ethylbenzene	0.001 %	C2H5C6H5	100-41-4	Listed	202-849-4
Styrene	0.001 %	C6H5CH=CH2	100-42-5	Listed	202-851-5
n-Tetradecane	0.001 %	CH3(CH2)12CH3	629-59-4	Listed	211-096-0
Dibutyl phthalate	0.001 %	C6H4[COO(CH2)3CH3]2	84-74-2	Listed	201-557-4
Di-2-ethylhexyl phthalate	0.001 %	C6H4(COOC8H17)2	117-81-7	Listed	204-211-0

4. FIRST AID MEASURES	
GENERAL ADVICE	: Consult a physician. Show this safety data sheet to the doctor in attendance.
INHALATION	: Move victim to fresh air. If breathing is difficult, give oxygen. If irritation persists, consult a physician.
SKIN CONTACT	: Remove contaminated clothes and shoes, rinse skin with plenty of water or shower. Use soap to help assure removal. Consult a physician immediately.
EYE CONTACT	: Flush eyes well with flooding large amounts of running water for at least 15 minutes. Assure adequate flushing by separating the eyelids with sterile fingers. If possible, remove any contact lenses. Consult a physician immediately.
INGESTION	: Rinse mouth, give plenty of water to dilute the substance. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician immediately.
GENERAL ADVICE	: Wash off immediately with soap and plenty of water. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious

protective suit. Use personal protective equipment.

PRODUCT NAME: Car Interior VOC Standard Mixed Sample 10µg/m in Ethanol

SDS No.1021-58011 Date June 21, 2023 3/6 page

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

FIRE & EXPLOSION HAZARDS : Toxic, irritating, dust/fume/smoke may be emitted. Carbon monoxide may be

foamed

SPECIAL PROTECTIVE EQUIPMENT

FOR FIRE FIGHTERS: Firemen should wear normal protective equipment(full bunker gear) and

positive-pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS : Remove ignition sources and ventilate the area. In case of insufficient ventilation,

wear suitable respiratory equipment. Avoid raising dust and avoid contact with

skin and eyes.

ENVIRONMENTAL PRECATIONS : Prevent further leakage or spillage if safe to do so. Do not let product enter

drains. Discharge into the environment must be avoided.

METHODS FOR CLEAN UP : Do not touch spilled material without suitable protection. Pick up and arrange

disposal without creating dust. Sweep up and shovel. Keep in suitable, closed

containers for disposal.

7. HANDLING AND STORAGE

HANDLING : Keep away from ignition sources and ventilate the area -No smoking. In case

of insufficient ventilation, wear suitable respiratory equipment.

Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapour or mist. Avoid prolonged or repeated exposure. Handle this product with suitable

protection.

STORAGE : Store away from sunlight, heat and all ignition sources in well-ventilated dry

place. Keep container tightly closed. Keep cool($2 \sim 10^{\circ}$ C).

INCOMPATIBLE PRODUCTS : Strong oxidizers, acids

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING MEASURES : Use exhaust ventilation to keep airborne concentrations below exposure limits.

Use adequate ventilation.

VENTILATION : Local Exhaust ; Necessary, Mechanical(General) ; Necessary

PERSONAL PROTECTION

Respiratory protection : Use respirators approved under appropriate government standards and follow

all regulations.

HAND PROTECTION : Chemical resistant gloves
EYE PROTECTION : Safety glasses(goggles)
SKIN PROTECTION : Protective clothing

CONTROL PARAMETERS

CHEMICAL NAME	ACGIH	OSHA Final Limits	NIOSH REL	
Ethanol	TWA= 1000 ppm	TWA= 1000 ppm	TWA= 1000 ppm	
Toluene	20 ppm	TWA 200 ppm	TWA 100 ppm	
o-Xylene	100 ppm	100 ppm	TWA 100 ppm	
m-Xylene	100 ppm	100 ppm	TWA 100 ppm	
p-Xylene	100 ppm	100 ppm	TWA 100 ppm	
Ethylbenzene	100 ppm	TWA 100 ppm	TWA 100 ppm	
Styrene	20 ppm	TWA 100 ppm	TWA 50 ppm	
n-Tetradecane	Not established			
Dibutyl phthalate	5 mg/m³	TWA 5 mg/m ³	TWA 5 mg/m ³	
Di-2-ethylhexyl phthalate	5 mg/m ³	TWA 5 mg/m ³	Ca TWA 5 mg/m ³	

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE : Liquid

COLOUR : Colorless, clear
ODOR : Characteristic odor

MELTING POINT / FREEZING POINT

: -117 °C(Ethanol)

BOILING POINT OR INITIAL BOILING POINT AND BOILING RANGE

: approx.78 °C(Ethanol)

PRODUCT NAME : Car Interior VOC Standard Mixed Sample 10µg/m L in Ethanol

SDS No.1021-58011 Date June 21, 2023 4/6 page

FLAMMABILITY : Flammable

LOWER AND UPPER EXPLOSION LIMIT / FLAMMABILITY LIMIT

: 3.3% (lower), 19 % (upper)(Ethanol)

FLASH POINT : 12.8 °C (TCC)(Ethanol)
AUTO-IGNITION TEMPERATURE : 371 - 427 °C(Ethanol)

DECOMPOSITION TEMPERATURE

: No data available(Ethanol)

pH : No data available KINEMATIC VISCOSITY : Not applicable

SOLUBILITY

Water : Miscible
Organic solvent : Miscible

PARTITION COEFFICIENT n-octanol/water (log value)

: log Pow: -0.32(Ethanol)

VAPOR PRESSURE : 5.33 kPa (at 20°C)(Ethanol)

DENSITY AND/OR RELATIVE DENSITY

: 0.81 g/cm³ (at 20°C)(Ethanol)

RELATIVE VAPOUR DENSITY : 1.6(Ethanol)
PARTICLE CHARACTERISTICS : Not applicable

10. STABILITY AND REACTIVITY

REACTIVITY : Stable under recommended storage conditions.

CHEMICAL STABILITY : Reacts with strong oxidizers.

CONDITION TO AVOID : Sunlight, heat, open flames, high temperature, sparks, static electrical charge,

other ignition sources, moisture

INCOMPATIBILE MATERIALS : Oxidizers and strong acids

HAZARDOUS DECOMPOSITION PRODUCTS

: CO, CO₂ may be formed.

11. TOXICOLOGICAL INFORMATION

This product is classified according to the classification of Ethanol.

We show the hazard information of Ethanol below.

ACUTE TOXICITY (Oral) : Rat LD50=6,200~17,800mg/kg.

ACUTE TOXICITY (Dermal) : Rabbit LDLo=20,000mg/kg.

ACUTE TOXICITY (Inhalation: Vapors)

: Rat LD50=66,280ppmV.

ACUTE TOXICITY (Inhalation: Dusts and mists)

: No data available.

SKIN CORROSION/IRRITATION : In a 4-hour exposure study on rabbits (OECD TG 404), the average score for

erythema was 1.0 at 1 and 24 hours after application, and at other time points the average scores for erythema and edema were all 0.0, with a "no irritation"

rating SIDS (2005).

EYE DAMAGE/EYE IRRITATION : It has been rated as moderately irritating in two Draize studies with rabbits

(OECD TG 405) (SIDS (2005)).

SKIN SENSITIZATION : In humans, there have been case reports of contact dermatitis, etc. due to

allergic reactions to alcohol (DFGOT vol. 12 vol. 12 (1999)).

GERM CELL MUTAGENICITY : As in vitro mutagenicity tests, the Ames test, the mouse phosphor test using

mammalian cultured cells, and the micronucleus test were all evaluated as negative (PATTY (6th, 2012), IARC (2010), DFGOT vol. 12 (1999), SIDS (2005), NTP DB (Access on June 2013), and all other in vitro chromosome aberration studies were also negative except for one positive result in a study using CHO

cells (SIDS (2005), PATTY (6th, 2012), IARC (2010)).

CARCINOGENICITY : ACGIH: Group A3(ACGIH(7th,2012)), it was clarified that Ethanol included in

alcohol drinks and its main metabolite, Acetaldehyde, induce a cancer of such

as esophagus.(IARC,2010)

REPRODUCTIVE TOXICITY : Human; fetal alcohol syndrome(PATTY(6th,2012)

SPECIFIC TARGET ORGAN TOXICITY - single exposure -

: Effect or damage to human. (PATTY(6th,2009), SIDS(2005))

PRODUCT NAME: Car Interior VOC Standard Mixed Sample 10µg/m in Ethanol

SDS No.1021-58011 Date June 21, 2023 5/6 page

SPECIFIC TARGET ORGAN TOXICITY - repeated exposure -

Serious damage to all human organs, especially in liver. (DFGOT vol.12 1999), HSDB

(Access on June 2013), SIDS(2005), PATTY(6th,2012))

ASPIRATION HAZARD : This mixture is not classified.

12. ECOLOGICAL INFORMATION

HAZARDOUS TO THE AQUATIC ENVIRONMENT Short-term (acute)

: This mixture is not classified.

(Fish) : 4.02 mg/L (Ethylbenzene), 0.35 mg/L (Dibutyl phthalate)

(Crustacea) : 0.4 mg/L (Ethylbenzene), 3.78 mg/L (Toluene), 2.3 mg/L (m-Xylene), 1.7 mg/L

(p-Xylene)

(Algae) : 0.8 mg/L (o-Xylene)

HAZARDOUS TO THE AQUATIC ENVIRONMENT Long-term (chronic)

: This mixture is not classified.

BIOACCUMULATIVE POTENTIAL : No data available MOBILITY IN SOIL : No data available No data available

HAZARDOUS TO THE OZONE LAYER

Not listed in Montreal Protocol list.

13. DISPOSAL INFORMATION

Dispose in a hazardous-waste site in accordance with all applicable regulations. Any disposal practice must be in compliance with country, local, state, and federal laws and regulations (contact country, local or state environment agency for specific rules).

14. TRANSPORT INFORMATION

International Regulations

Marine regulatory information : Comply the provisions of IMO.

UN Number : 1170

Proper Shipping Name : ETHANOL SOLUTION Class : 3, flammable liquid

Packing Group : II

Marine Pollutant : Not applicable

Aviation regulatory information : Comply the previsions of ICAO/IATA.

UN Number : 1170

Proper Shipping Name : ETHANOL SOLUTION Class : 3, flammable liquid

Packing Group : II

Regulations in Japan

Land regulatory information : Not applicable

Marine regulatory information : Comply the provisions of the Ship Safety Act..

UN Number : 1170

Proper Shipping Name : Ethanol solution
Class : 3, flammable liquid

Packing Group : II

Marine Pollutant : Not applicable

Aviation regulatory information : Comply the previsions of the Civil Aeronautics Act.

UN Number : 1170

Proper Shipping Name : Ethanol solution
Class : 3, flammable liquid

Packing Group : II Emergency Response Guide Number : 127

15. REGULATORY INFORMATION

US REGULATIONS : Labeling according to EC Directives; See section 2
EU REGURATIONS : Labeling according to EC Directives; See section 2

PRODUCT NAME: Car Interior VOC Standard Mixed Sample 10µg/m in Ethanol

SDS No.1021-58011 Date June 21, 2023 6/6 page

16. OTHER INFORMATION

NOTICE:

The information contained in the SDS description is applicable exclusively to the chemical substance identified herein and for its intended use as an analytical reference standard or reagent and to the unit quantity intended for that purpose. The information does not relate to, and may not be appropriate for, any application or larger quantity of the substance described. Our products are intended for the use by individuals possessing sufficient technical skill and qualification on use the material potential hazardous chemical. Accordingly, no representation or warranty, express or implied, with respect to merchantability and fitness for a particular purpose is made with respect to the information contained herein. Attention:

This product in terms of chemical identity and the unit amount provide is intended for use in chemical analysis and not for human consumption, nor any other purpose.